



## Hydrogen Generator for Auto Car/ Truck /Diesel Generator Set As Fuel Saver

**Our Patent Design generator is very efficient! It saves 60-80% fuel, and reduce over 75% emission! And improve 35-75% power of (car) engine.**

Hydrogen can both supply energy directly and **stimulate fuel burning** in engine! Using hydrogen as a **combustion stimulant** makes it possible for other fuels to save and lower down exhaust emissions and increase mileage.

We did tests, for example: 100KM, first fulfill engine diesel tank,  
First round we burn 46 RMB diesel WITHOUT HYDROGEN GENERATOR;  
After We USE HYDROGEN GENERATOR, this 100KM only burn 20 RMB diesel!!!!!!

**Save over 60% diesel!!!!!! Almost the same with petrol engines!!!!!!**

**And also can be used in large engines like large diesel electricity generator sets etc, saving over 50%. It also can be used in cutting and welding applications!**

Input Voltage: 12-24V Input current: 3-155A

Life: 20years Warranty: 5 years, actually lifetime free repair.

We have different sizes for different power engine. We can also make according to customer's demand. It can be used in any engine cc.

Hydrogen & Oxygen gas output: usually 800-100000ml, slightly vary depends the solution density in distilled water.



## FOB Price List For Hydrogen & Oxygen Generator For Auto

Type	Model S-1.5 (Plastic shell)	Model S48L (Stainless Steel shell)	Model S-60L (Stainless Steel shell)	Model S90L (Stainless Steel shell)	Model S120L (Stainless Steel shell)	Model S180L (Stainless Steel shell)	Model S300L (Stainless Steel shell)	Model S600L (Stainless Steel shell)	Model S1200L (Stainless Steel shell)	Model S3000L	
Input voltage	12V--24V										
Current range(A)	3-8	3-8	3-10	5-18	5-25	8-30	12-45	50—150	60—180	200-350	
Output Hydroxyl (ml per min /Liters per hour)	600 ml/min 36 L/H	800ml/min 48L/H	1000 ml/min 60 L/H	1500 ml/min 90 L/H	2000 ml/min 120 L/H	3000 ml/min 180 L/H	5000 ml/min 300 L/H	10000 ml/min 600 L/H	20000 ml/min 1200 L/H	50000ml/min 3000L/H	
Shortcut-power-off	current breaker										
Average saving	15-20%	18-25%	20-35%	25-40%	45-50%	50-65%	50-70%	60-75%	70-80%	60-80%	
Generator temperature when working	30-50									40-50	
dimension(cm):	9*9*25	9*9*25	17*9.5*25	17*9.5*25	12.5*28*35	12.5*28*35	21*30*35	21*40*35	40*42*35	65X85X110	
Weight (KG)	2.5	2.8	3.8	5.0	6.0	6.5	12	25	35	125	
Unit price	1000pcs +++	71.5	143	195	221	377	429	715	1105	2015	5395
USD	100-1000pcs	84.5	156	234	260	416	468	780	1170	2080	5525
EXW	10- 100pcs	130	162.5	260	325	455	507	845	1235	2145	6175

- 📍 Cairo, EGYPT. 3 Abou Tamam st., Hadayak El Kobba. (+2) 02 233 023 99 (+2) 01 22 22 00 787
- 📍 Shenzhen, CHINA. 1709B Saige st., Hua Qlang Bel, Futian District.
- 📍 Kowloon, Hong Kong. 5/f Hang Pont Commercial Building ., 31 Tonkin st., Cheung Sha Wan.
- 📍 Vietnam : 0084-1688370651 📍 Malaysia : (+6)13416407902 📍 Kuwwait : (+9)6560617291 📍 Sudan : (+2)49910745498



SANTS سانس  
جروب GROUP

BRINGING YOUR DREAMS TO REALITY

### Model S-1.5

<u>Input voltage</u>	<u>12V--24V</u>
<u>Current range(A)</u>	<u>5-25</u>
<u>Output Hydroxy (ml/min)</u>	<u>1-1.5L/min (60 liter/ hour)</u>
<u>Shortcut-power-off mileage</u>	<u>current breaker 55-175%</u>
<u>improvement</u>	
<u>Working temperature</u>	<u>30-50</u>
<u>Dimension(cm):</u>	<u>22*25*30</u>
<u>Net Weight (KG)</u>	<u>7.0</u>

- 📍 Cairo, EGYPT. 3 Abou Tamam st., Hadayak El Kobba. (+2) 02 233 023 99 (+2) 01 22 22 00 787
- 📍 Shenzhen, CHINA. 1709B Saige st., Hua Qlang Bel, Futian District.
- 📍 Kowloon, Hong Kong. 5/f Hang Pont Commercial Building ., 31 Tonkin st., Cheung Sha Wan.
- 📍 Vietnam : 0084-1688370651 📍 Malaysia : (+6)13416407902 📍 Kuwwait : (+9)6560617291 📍 Sudan : (+2)49910745498



SANTS سانس  
جروب GROUP  
BRINGING YOUR DREAMS TO REALITY

### Model S48L

<u>Input voltage</u>	<u>12V--24V</u>
<u>Current range(A)</u>	<u>3-8</u>
<u>Output Hydroxy (ml/min)</u>	<u>800 ml/min (48 liter/ hour)</u>
<u>Shortcut-power-off mileage improvement</u>	<u>current breaker</u>
<u>Working temperature</u>	<u>35-100%</u>
<u>Dimension(cm):</u>	<u>30-50</u>
<u>Net Weight (KG)</u>	<u>D10 H20 (round)</u>
	<u>1.5</u>



- 📍 Cairo, EGYPT. 3 Abou Tamam st., Hadayak El Kobba. (+2) 02 233 023 99 (+2) 01 22 22 00 787
- 📍 Shenzhen, CHINA. 1709B Saige st., Hua Qlang Bel, Futian District.
- 📍 Kowloon, Hong Kong. 5/f Hang Pont Commercial Building ., 31 Tonkin st., Cheung Sha Wan.
- 📍 Vietnam : 0084-1688370651 📍 Malaysia : (+6)13416407902 📍 Kuwait : (+9)6560617291 📍 Sudan : (+2)49910745498



[www.santsgroup.com](http://www.santsgroup.com)



[info@santsgroup.com](mailto:info@santsgroup.com)



### Model S-60L

<u>Input voltage</u>	<u>12V--24V</u>
<u>Current range(A)</u>	<u>3-10</u>
<u>Output Hydroxy (ml/min)</u>	<u>1000 ml/min (60 liter/ hour)</u>
<u>Shortcut-power-off mileage improvement</u>	<u>current breaker</u> <u>50-100%</u>
<u>Working temperature</u>	<u>30-50</u>
<u>Dimension(cm):</u>	<u>17*9*25 (rectangular)</u>
<u>Net Weight (KG)</u>	<u>2.8</u>







SANTS سانس  
جروب GROUP  
BRINGING YOUR DREAMS TO REALITY

### Model S90L

<u>Input voltage</u>	<u>12V--24V</u>
<u>Current range(A)</u>	<u>5-18</u>
<u>Output Hydroxy (ml/min)</u>	<u>1500 ml/min (90 liter/ hour)</u>
<u>Shortcut-power-off</u>	<u>current breaker</u>
<u>mileage improvement</u>	<u>50-120%</u>
<u>Working temperature</u>	<u>30-50</u>
<u>Dimension(cm):</u>	<u>17*9*25 (rectangular)</u>
<u>Net Weight (KG)</u>	<u>3.0</u>



- 📍 Cairo, EGYPT. 3 Abou Tamam st., Hadayak El Kobba. (+2) 02 233 023 99 (+2) 01 22 22 00 787
- 📍 Shenzhen, CHINA. 1709B Saige st., Hua Qlang Bel, Futian District.
- 📍 Kowloon, Hong Kong. 5/f Hang Pont Commercial Building ., 31 Tonkin st., Cheung Sha Wan.
- 📍 Vietnam : 0084-1688370651 📍 Malaysia : (+6)13416407902 📍 Kuwwait : (+9)6560617291 📍 Sudan : (+2)49910745498



SANTS سانس جروب  
GROUP

BRINGING YOUR DREAMS TO REALITY

### Model S120L

<u>Input voltage</u>	<u>12V--24V</u>
<u>Current range(A)</u>	<u>5-25</u>
<u>Output Hydroxy (ml/min)</u>	<u>2000 ml/min (120 liter/ hour)</u>
<u>Shortcut-power-off mileage improvement</u>	<u>current breaker</u> <u>50-150%</u>
<u>Working temperature</u>	<u>30-50</u>
<u>Dimension(cm):</u>	<u>17*9*25 (rectangular)</u>
<u>Net Weight (KG)</u>	<u>3.0</u>



- 📍 Cairo, EGYPT. 3 Abou Tamam st., Hadayak El Kobba. (+2) 02 233 023 99 (+2) 01 22 22 00 787
- 📍 Shenzhen, CHINA. 1709B Saige st., Hua Qlang Bel, Futian District.
- 📍 Kowloon, Hong Kong. 5/f Hang Pont Commercial Building ., 31 Tonkin st., Cheung Sha Wan.
- 📍 Vietnam : 0084-1688370651 📍 Malaysia : (+6)13416407902 📍 Kuwwait : (+9)6560617291 📍 Sudan : (+2)49910745498



SANTS سانس  
جروب GROUP  
BRINGING YOUR DREAMS TO REALITY

### Model S180L

<u>Input voltage</u>	<u>12V--24V</u>
<u>Current range(A)</u>	<u>5-25</u>
<u>Output Hydroxy (ml/min)</u>	<u>3000 ml/min (180 liter/ hour)</u>
<u>Shortcut-power-off mileage</u>	<u>current breaker</u>
<u>improvement</u>	<u>55-175%</u>
<u>Working temperature</u>	<u>30-50</u>
<u>Dimension(cm):</u>	<u>22*12*35 (rectangular)</u>
<u>Net Weight (KG)</u>	<u>7.0</u>



- 📍 Cairo, EGYPT. 3 Abou Tamam st., Hadayak El Kobba. (+2) 02 233 023 99 (+2) 01 22 22 00 787
- 📍 Shenzhen, CHINA. 1709B Saige st., Hua Qlang Bel, Futian District.
- 📍 Kowloon, Hong Kong. 5/f Hang Pont Commercial Building ., 31 Tonkin st., Cheung Sha Wan.
- 📍 Vietnam : 0084-1688370651 📍 Malaysia : (+6)13416407902 📍 Kuwwait : (+9)6560617291 📍 Sudan : (+2)49910745498





### Model S300L

<u>Input voltage</u>	<u>12V--24V</u>
<u>Current range(A)</u>	<u>10-30</u>
<u>Output Hydroxy (ml/min)</u>	<u>5000 ml/min (300 liter/hour)</u>
<u>Shortcut-power-off mileage improvement</u>	<u>current breaker</u>
<u>Working temperature</u>	<u>100-200%</u>
<u>Dimension(cm):</u>	<u>30-50</u>
<u>Net Weight (KG)</u>	<u>21*25*35 (rectangular)</u>
	<u>10</u>





### Model S600L

<u>Input voltage</u>	<u>12V--24V</u>
<u>Current range(A)</u>	<u>25-45</u>
<u>Output Hydroxy (ml/min)</u>	<u>10000 ml/min (600 liter/hour)</u>
<u>Shortcut-power-off mileage improvement</u>	<u>current breaker</u> <u>150-250%</u>
<u>Working temperature</u>	<u>Especially suitable for large diesel engine</u> <u>35-55</u>
<u>Dimension(cm):</u>	<u>21*30*35</u>
<u>Net Weight (KG)</u>	<u>16</u>





### Model S1200L

<u>Input voltage</u>	<u>12V--24V</u>
<u>Current range(A)</u>	<u>25-45</u>
<u>Output Hydroxy (ml/min)</u>	<u>20000 ml/min (1200 liter/hour)</u>
<u>Shortcut-power-off mileage improvement</u>	<u>current breaker</u> <u>175-300%,</u>
	<b><u>Especially suitable for large diesel engine</u></b>
<u>Working temperature</u>	<u>35-55</u>
<u>Dimension(cm):</u>	<u>38*42*35</u>
<u>Net Weight (KG)</u>	<u>25</u>





### Model S3000L

<u>Input voltage</u>	<u>12V--24V</u>
<u>Current range(A)</u>	<u>200-350</u>
<u>Output Hydroxy (ml/min)</u>	<u>50000 ml/min (3000 liter/ hour)</u>
<u>Shortcut-power-off</u>	<u>current breaker</u>
<u>mileage improvement</u>	<u>65-265%</u>
<u>Working temperature</u>	<u>30-50</u>
<u>Dimension(cm):</u>	<u>75X100X110</u>
<u>Weight (KG)</u>	<u>145</u>

