



40 inches D-LED TV

Model Photo



Model No.	SIT 200
Scaler	MST
Interface	D-LED
Size & Aspect Ratio	40"(16:9)
Pixel Pitch	0.46125(H) x 0.15375(V)mm
Active area	885.6(H) X 498.15(V) mm
Max. Color	16.7M (8Bit)
Resolution	1920 x 1080
Contrast Ratio	5000:1
Brightness	200cd/m²
View Angle(CR≥10)	178°/178°(UP/DOWN LEFT/RIGHT)



LED backlight life	500,00hours
Response Time(Typ)	6.5ms
TV Standard & Set Up	
Tuner	x 1
DTV SYSTEM	VHF (174MHz - 230MHz)UHF (474MHz - 862MHz);7MHz/8MHz;COFDM 2K/8K QPSK, 16QAM,64QAM;MPEG-2 MP@Hlor MPEG-4 AVC/H.264
Video System	PAL/SECAM/NTSC-3.58,NTSC-4.43,PAL-60
Sound System	B/G, D/K, I,L,L',M.N
Audio	
Sound Effect	MTS, Spatial Stereo, Dynamic Bass
Sound output	10W X2
SOUND SYSTEM	B/G;D/K;l;L/L
STEREO SYSTEM	YES
NICAM	YES
VIDEO	
TV SYSTEM	pal/secam/NTSC
DTV SYSTEM	DVB-T(MPEG2,MPEG4,MHEG5)
HDTV Compatible	480p, 576p, 720p, 1080i.1080p
Teletext(Page)	1000PAGES
Deinterlace / Comb filter	3D
3D Video Noise Reduction	YES
OSD LANGUAGE	English/French/German/Spanish/Italian/Dutch/Portugues e
Connectors	
AV	x2
S-VIDEO	x1
SCart	x1(optional)
VGA	x1
HDMI	x3
DVI	NO



SANTS سانس
جروب GROUP
BRINGING YOUR DREAMS TO REALITY

Coax digital output	x1
Stereo mini jack input	x1
RCA input	x2
CI slot	x1(optional)
USB	X1(USB PVR,MPEG1, MPEG2,MP3, WMA,JPEG);optional for *.AVI *.MKV *.ASF *.WMV *.MOV *.MP4 *.VOB *.MPG *.PS *.TS
Analog tuner	x1
DVB-T	optional
ATSC tuner	optional
DVD	NO
YPbPr or YCbCr (COMPONENT)	x1
Headphone	x1
other Features	
Auto Power off	yes
Sleep Timer	yes
Clock	yes
Consumption	Standby: 1 watt/ Operating: less than 75Watt
Safety	CE/ROHS/FCC
UNIT/Carton Size	940*155*640mm
Net/Gross Weight	12/13kgs
Loading Capacity 20"/40"/40"HQ	300pcs/516pcs/720pcs



Model Photo



Model No.	SIT 210
Scaler	MST
Interface	D-LED
Size & Aspect Ratio	40"(16:9)
Pixel Pitch	0.46125(H) x 0.15375(V)mm
Active area	885.6(H) X 498.15(V) mm
Max. Color	16.7M (8Bit)
Resolution	1920 x 1080
Conrrast Ratio	5000:1
Brightness	200cd/m²
View Angle(CR≥10)	178°/178°(UP/DOUN LEFT/RIGHT)



LED backlight life	500,00hours
Response Time(Typ)	6.5ms
TV Standard & Set Up	
Tuner	x 1
DTV SYSTM	VHF (174MHz - 230MHz)UHF (474MHz - 862MHz);7MHz/8MHz;COFDM 2K/8K QPSK, 16QAM,64QAM;MPEG-2 MP@Hlor MPEG-4 AVC/H.264
Video System	PAL/SECAM/NTSC-3.58,NTSC-4.43,PAL-60
Sound System	B/G, D/K, I,L,L',M.N
Audio	
Sound Effect	MTS, Spatial Stereo, Dynamic Bass
Sound output	10W X2
SOUND SYSTEM	B/G;D/K;I;L/L
STEREO SYSTEM	YES
NICAM	YES
VIDEO	
TV SYSTEM	pal/secam/NTSC
DTV SYSTEM	DVB-T(MPEG2,MPEG4,MHEG5)
HDTV Compatible	480p, 576p, 720p, 1080i.1080p
Teletext(Page)	1000PAGES
Deinterlace / Comb filter	3D
3D Video Noise Reduction	YES
OSD LANGUAGE	English/French/German/Spanish/Italian/Dutch/Portuguese
Connectors	
AV	x2
S-VIDEO	x1
SCart	x1(optional)
VGA	x1
HDMI	x3
DVI	NO



Coax digital output	x1
Stereo mini jack input	x1
RCA input	x2
CI slot	x1(optional)
USB	X1(USB PVR,MPEG1, MPEG2,MP3, WMA,JPEG);optional for *.AVI *.MKV *.ASF *.WMV *.MOV *.MP4 *.VOB *.MPG *.PS *.TS
Analog tuner	x1
DVB-T	optional
ATSC tuner	optional
DVD	NO
YPbPr or YCbCr (COMPONENT)	x1
Headphone	x1
other Features	
Auto Power off	yes
Sleep Timer	yes
Clock	yes
Consumption	Standby: 1 watt/ Operating: less than 75Watt
Safety	CE/ROHS/FCC
UNIT/Carton Size	940*155*640mm
Net/Gross Weight	12/13kgs
Loading Capacity 20"/40"/40"HQ	300pcs/516pcs/720pcs



SANTS سانس
جروب GROUP
BRINGING YOUR DREAMS TO REALITY.

Model Photo



Model No.	SIT 220
Scaler	MST
Interface	D-LED
Size & Aspect Ratio	40"(16:9)
Pixel Pitch	0.46125(H) x 0.15375(V)mm
Active area	885.6(H) X 498.15(V) mm
Max. Color	16.7M (8Bit)
Resolution	1920 x 1080
Conrrast Ratio	5000:1
Brightness	200cd/m²
View Angle(CR≥10)	178°/178°(UP/DOUN LEFT/RIGHT)
LED backlight life	500,00hours



Response Time(Typ)	6.5ms
TV Standard & Set Up	
Tuner	x 1
DTV SYSTM	VHF (174MHz – 230MHz)UHF (474MHz - 862MHz);7MHz/8MHz
Video System	2K/8K QPSK, 16QAM,64QAM;MPEG-2 MP@Hlor MPEG-4 AV
Sound System	PAL/SECAM/NTSC-3.58,NTSC-4.43,PAL-60
Audio	B/G, D/K, I,L,L',M.N
Sound Effect	MTS, Spatial Stereo, Dynamic Bass
Sound output	10W X2
SOUND SYSTEM	B/G;D/K;I;L/L
STEREO SYSTEM	YES
NICAM	YES
VIDEO	
TV SYSTEM	pal/secam/NTSC
DTV SYSTEM	DVB-T(MPEG2,MPEG4,MHEG5)
HDTV Compatible	480p, 576p, 720p, 1080i.1080p
Teletext(Page)	1000PAGES
Deinterlace / Comb filter	3D
3D Video Noise Reduction	YES
OSD LANGUAGE	English/French/German/Spanish/Italian/Dutch/Portuguese
Connectors	
AV	x2
S-VIDEO	x1
SCart	x1(optional)
VGA	x1
HDMI	x3
DVI	NO



Coax digital output	x1
Stereo mini jack input	x1
RCA input	x2
CI slot	x1(optional)
USB	X1(USB PVR,MPEG1, MPEG2,MP3, WMA,JPEG);optional for *.ASF *.WMV *.MOV *.MP4 *.VOB *.MPG *.PS *.TS
Analog tuner	x1
DVB-T	optional
ATSC tuner	optional
DVD	NO
YPbPr or YCbCr (COMPONENT)	x1
Headphone	x1
other Features	
Auto Power off	yes
Sleep Timer	yes
Clock	yes
Consumption	Standby: 1 watt/ Operating: less than 75Watt
Safety	CE/ROHS/FCC
UNIT/Carton Size	940*155*640mm
Net/Gross Weight	12/13kgs

📍 Cairo, EGYPT. 3 Abou Tamam st., Hadayak El Kobba. (+2) 02 233 023 99 (+2) 01 22 22 00 787

📍 Shenzhen, CHINA. 1709B Saige st., Hua Qiang Bel, Futian District.

📍 Kowloon, Hong Kong. 5/f Hang Pont Commercial Building ., 31 Tonkin st., Cheung Sha Wan.

📍 Vietnam : 0084-1688370651 📍 Malaysia : (+6)13416407902 📍 Kuwait : (+9)6560617291 📍 Sudan : (+2)49910745498



Model Photo

42 inches D-LED TV



Model No.	SIT 300
Back Light	D-LED
Scaler	MST
Interface	LED
Size & Aspect Ratio	42"(16:9)
Pixel Pitch	0.15125(H) x 0.46125(V)
Active area	952.0(H)×551.0(V)mm
Max. Color	1.06B
Resolution	1920 x 1080
Conrrast Ratio	5000:1
Brightness	200cd/m²
View Angle(CR≥10)	178°(H)/178°(V)



LED backlight life	100,000hours
Response Time(Typ)	5ms
TV Standard & Set Up	
Tuner	x 1
DTV SYSTEM	VHF (174MHz – 230MHz)UHF (474MHz - 862MHz);7MHz/8MHz;COFDM 2K/8K QPSK, 16QAM,64QAM;MPEG-2 MP@Hlor MPEG-4 AVC/H.264
Video System	PAL/SECAM/NTSC-3.58,NTSC-4.43,PAL-60
Sound System	B/G, D/K, I,L,L',M.N
Audio	
Sound Effect	MTS, Spatial Stereo, Dynamic Bass
Sound output	10W X2
SOUND SYSTEM	B/G;D/K;I;L/L
STEREO SYSTEM	YES
NICAM	YES
VIDEO	
TV SYSTEM	pal/secam/NTSC
DTV SYSTEM	DVB-T(MPEG2,MPEG4,MHEG5)
HDTV Compatible	480p, 576p, 720p, 1080i.1080p
Teletext(Page)	500PAGES
Deinterlace / Comb filter	3D
3D Video Noise Reduction	YES
OSD LANGUAGE	English/French/German/Spanish/Italian/Dutch/Portuguese
Connectors	
AV	x2
S-VIDEO	x1
SCart	x1(optional)



VGA	x1
HDMI	x3
DVI	NO
Coax digital output	x1
Stereo mini jack input	x1
RCA input	x2
CI slot	x1(optional)
USB	X1(USB PVR,MPEG1, MPEG2,MP3, WMA,JPEG);optional for *.AVI *.MKV *.ASF *.WMV *.MOV *.MP4 *.VOB *.MPG *.PS *.TS
Analog tuner	x1
DVB-T	optional
ATSC tuner	optional
DVD	NO
YPbPr or YCbCr (COMPONENT)	x1
Headphone	x1
other Features	
Auto Power off	yes
Sleep Timer	yes
Clock	yes
Consumption	Standby: 1 watt/ Operating: less than 140Watt
Safety	CE/ROHS/FCC
Carton Size	1180*145*687mm
Net/Gross Weight	12kg/14kg
Loading Capacity 20"/40"/40"HQ	226pcs/466pcs/534pcs



Model Photo



Model No.	SIT 310
Back Light	D-LED
Scaler	MST
Interface	LED
Size & Aspect Ratio	42"(16:9)
Pixel Pitch	0.15125(H) x 0.46125(V)
Active area	952.0(H)×551.0(V)mm
Max. Color	1.06B
Resolution	1920 x 1080
Contrast Ratio	5000:1
Brightness	200cd/m²
View Angle(CR≥10)	178°(H)/178°(V)



LED backlight life	100,000hours
Response Time(Typ)	5ms
TV Standard & Set Up	
Tuner	x 1
DTV SYSTEM	VHF (174MHz - 230MHz)UHF (474MHz - 862MHz);7MHz/8MHz;COFDM 2K/8K QPSK, 16QAM,64QAM;MPEG-2 MP@Hlor MPEG-4 AVC/H.264
Video System	PAL/SECAM/NTSC-3.58,NTSC-4.43,PAL-60
Sound System	B/G, D/K, I,L,L',M.N
Audio	
Sound Effect	MTS, Spatial Stereo, Dynamic Bass
Sound output	10W X2
SOUND SYSTEM	B/G;D/K;I;L/L
STEREO SYSTEM	YES
NICAM	YES
VIDEO	
TV SYSTEM	pal/secam/NTSC
DTV SYSTEM	DVB-T(MPEG2,MPEG4,MHEG5)
HDTV Compatible	480p, 576p, 720p, 1080i.1080p
Teletext(Page)	500PAGES
Deinterlace / Comb filter	3D
3D Video Noise Reduction	YES
OSD LANGUAGE	English/French/German/Spanish/Italian/Dutch/Portuguese
Connectors	
AV	x2
S-VIDEO	x1
SCart	x1(optional)
VGA	x1
HDMI	x3
DVI	NO

📍 Cairo, EGYPT. 3 Abou Tamam st., Hadayak El Kobba. (+2) 02 233 023 99 (+2) 01 22 22 00 787

📍 Shenzhen, CHINA. 1709B Saige st., Hua Qiang Bel, Futian District.


📍 Kowloon, Hong Kong. 5/f Hang Pont Commercial Building ., 31 Tonkin st., Cheung Sha Wan.

📍 Vietnam : 0084-1688370651 📍 Malaysia : (+6)13416407902 📍 Kuwait : (+9)6560617291 📍 Sudan : (+2)49910745498



Coax digital output	x1
Stereo mini jack input	x1
RCA input	x2
CI slot	x1(optional)
USB	X1(USB PVR,MPEG1, MPEG2,MP3, WMA,JPEG);optional for *.AVI *.MKV *.ASF *.WMV *.MOV *.MP4 *.VOB *.MPG *.PS *.TS
Analog tuner	x1
DVB-T	optional
ATSC tuner	optional
DVD	NO
YPbPr or YCbCr (COMPONENT)	x1
Headphone	x1
other Features	
Auto Power off	yes
Sleep Timer	yes
Clock	yes
Consumption	Standby: 1 watt/ Operating: less than 140Watt
Safety	CE/ROHS/FCC
Carton Size	1180*145*687mm
Net/Gross Weight	12kg/14kg
Loading Capacity 20"/40"/40"HQ	226pcs/466pcs/534pcs



Model Photo	
Model No.	SIT 320
Back Light	D-LED
Scaler	MST
Interface	LED
Size & Aspect Ratio	42"(16:9)
Pixel Pitch	0.15125(H) x 0.46125(V)
Active area	952.0(H)×551.0(V)mm
Max. Color	1.06B
Resolution	1920 x 1080
Contrast Ratio	5000:1
Brightness	200cd/m ²
View Angle(CR≥10)	178°(H)/178°(V)



LED backlight life	100,000hours
Response Time(Typ)	5ms
TV Standard & Set Up	
Tuner	x 1
DTV SYSTEM	VHF (174MHz - 230MHz)UHF (474MHz - 862MHz);7MHz/8MHz;COFDM 2K/8K QPSK, 16QAM,64QAM;MPEG-2 MP@Hlor MPEG-4 AVC/H.264
Video System	PAL/SECAM/NTSC-3.58,NTSC-4.43,PAL-60
Sound System	B/G, D/K, I,L,L',M.N
Audio	
Sound Effect	MTS, Spatial Stereo, Dynamic Bass
Sound output	10W X2
SOUND SYSTEM	B/G;D/K;L/L
STEREO SYSTEM	YES
NICAM	YES
VIDEO	
TV SYSTEM	pal/secam/NTSC
DTV SYSTEM	DVB-T(MPEG2,MPEG4,MHEG5)
HDTV Compatible	480p, 576p, 720p, 1080i.1080p
Teletext(Page)	500PAGES
Deinterlace / Comb filter	3D
3D Video Noise Reduction	YES
OSD LANGUAGE	English/French/German/Spanish/Italian/Dutch/Portuguese
Connectors	
AV	x2
S-VIDEO	x1
SCart	x1(optional)
VGA	x1
HDMI	x3
DVI	NO



Coax digital output	x1
Stereo mini jack input	x1
RCA input	x2
CI slot	x1(optional)
USB	X1(USB PVR,MPEG1, MPEG2,MP3, WMA,JPEG);optional for *.AVI *.MKV *.ASF *.WMV *.MOV *.MP4 *.VOB *.MPG *.PS *.TS
Analog tuner	x1
DVB-T	optional
ATSC tuner	optional
DVD	NO
YPbPr or YCbCr (COMPONENT)	x1
Headphone	x1
other Features	
Auto Power off	Yes
Sleep Timer	Yes
Clock	Yes
Consumption	Standby: 1 watt/ Operating: less than 140Watt
Safety	CE/ROHS/FCC
Carton Size	1180*145*687mm
Net/Gross Weight	12kg/14kg
Loading Capacity 20"/40"/40"HQ	226pcs/466pcs/534pcs

📍 Cairo, EGYPT. 3 Abou Tamam st., Hadayak El Kobba. (+2) 02 233 023 99 (+2) 01 22 22 00 787

📍 Shenzhen, CHINA. 1709B Saige st., Hua Qiang Bel, Futian District.

📍 Kowloon, Hong Kong. 5/f Hang Pont Commercial Building ., 31 Tonkin st., Cheung Sha Wan.

📍 Vietnam : 0084-1688370651 📍 Malaysia : (+6)13416407902 📍 Kuwait : (+9)6560617291 📍 Sudan : (+2)49910745498



Picture		55 Inches D-LED TV
Model number		SIT 500
Display Feature	LED panel	55inch
	Display Size	1209.6(H)×680.4(V)mm
	Aspect ratio	16:9 FHD
	Resolution	1920(H)×1080(V) RGB
	Pixel Pitch	0.630(H) x 0.630(V)
	Maximum Colors	16.7M
	Horizontal Freq.	44KHz~53KHz
	Vertical Freq.	50Hz~66Hz
	Brightness	300 cd/m2
	Contrast	5000:1
	Viewing Angle	178°/178°(UP/DOWN LEFT/RIGHT)
	Response time	6ms
TV SYSTEM	COLOR SYSTEM	PAL,NTSC,SECAM
	Sound System	M,N,B/G,D/K,I
	Stereo System	Stereo




	V-CHIP	No	
	TELETEXT	Optional	
	STORAGE CHANNEL	200	
Video Features	Video Processing & Conversion	3D digital comb filter and 3D noise reduction function	
Audio Speaker System	Speaker Type	Inseparable	
	Maximum Audio Output	15W × 2	
	Sound multiplex circuit	Standard/Dynamic/Soft/User	
Terminals	Video in	RF:TV/CAT V 75ohms connector	1
		AV : RCA 75ohms composite video	3 RCA(Yellow,Red,White) and 1 mini AV jack
		S-Video : 4-pin DIN	1
		YPbPr: RCA	1
		HDMI	x2
		USB	1
	AUDIO IN	L/R RCA for YPbPr	No
		L/R RCA for S-Video& AV	1
		L/R RCA for S-Video& AV&YPbPr	1



		PC Audio in 3.5mm Jack:x1	1
	OUTPUT	Coaxial Audio output:	No
		EARPHONE OUTPUT	1
		AV OUTPUT	1
INPUT FORMAT	YPbPr		480i, 480P, 576i,720P, 720P, 1080iand 1080p
	HDMI		480i, 480P, 576i,720P, 720P, 1080iand 1080p
	PC		VGA 60/75Hz, SVGA 60/75Hz, XGA 60/75Hz, WXGA 60/75Hz, SXGA 60/75Hz
	AV/S-Video/SCART		640*480i 50Hz/60Hz
	USB	MUSIC	MP3/WMA/M4A/AAC
		Picture	JPEG/BMP/PNG
		Movie	MPEG1/MPEG2/MPEG4, RM, RMVB, MOV, MJPEG, Divx
		TXT	Optional
Other		Software upgrade	
Other Features			Support On/Off timer, Sleep timer etc
Remote Control function support for full OSD features			Remote control shortcut keys support: menu, signal source selection, electronic program guides, mute, etc. OSD menu support: English ,Portuguese,Spanish
Wall Mount			Optional
Power Supply	INPUT		110V-240V 50/60Hz
	Power Consumption		180W
	Power Saving		<1W
Certification			CE,CB,FCC,UL,Rohs
Accessories			remote control / user manual / power cord / battery
Mechanical	Package Dimension		1520*8700*185mm
Loading Qty	20GP/40GP/40HQ		120/242/282pcs



Picture		
Model number		SIT 510
Display Feature	LED panel	55inch
	Display Size	1209.6(H)×680.4(V)mm
	Aspect ratio	16:9 FHD
	Resolution	1920(H)×1080(V) RGB
	Pixel Pitch	0.630(H) x 0.630(V)
	Maximum Colors	16.7M
	Horizontal Freq.	44KHz~53KHz
	Vertical Freq.	50Hz~66Hz
	Brightness	300 cd/m2
	Contrast	5000:1
	Viewing Angle	178°/178°(UP/DOWN LEFT/RIGHT)
	Response time	6ms
COLOR SYSTEM		PAL,NTSC,SECAM



TV SYSTEM	Sound System		M,N,B/G,D/K,I
	Stereo System		Stereo
	V-CHIP		No
	TELETEXT		Optional
	STORAGE CHANNEL		200
Video Features	Video Processing & Conversion		3D digital comb filter and 3D noise reduction function
Audio Speaker System	Speaker Type		Inseparable
	Maximum Audio Output		15W × 2
	Sound multiplex circuit		Standard/Dynamic/Soft/User
Terminals	Video in	RF:TV/CAT V 75ohms connector	1
		AV : RCA 75ohms composite video	3 RCA(Yellow,Red,White) and 1 mini AV jack
		S-Video : 4-pin DIN	1
		YPbPr: RCA	1
		HDMI	x2
		USB	1
	AUDIO IN	L/R RCA for YPbPr	No
		L/R RCA for S-Video& AV	1
		L/R RCA for S-Video& AV&YPbPr	1
		PC Audio in 3.5mm Jack:x1	1



	OUTPUT	Coaxial Audio output:	No
		EARPHONE OUTPUT	1
		AV OUTPUT	1
INPUT FORMAT	YPbPr		480i, 480P, 576i, 720P, 720P, 1080i and 1080p
	HDMI		480i, 480P, 576i, 720P, 720P, 1080i and 1080p
	PC		VGA 60/75Hz, SVGA 60/75Hz, XGA 60/75Hz, WXGA 60/75Hz, SXGA 60/75Hz
	AV/S-Video/SCART		640*480i 50Hz/60Hz
	USB	MUSIC	MP3/WMA/M4A/AAC
		Picture	JPEG/BMP/PNG
		Movie	MPEG1/MPEG2/MPEG4, RM, RMVB, MOV, MJPEG, Divx
TXT		Optional	
	Other	Software upgrade	
Other Features		Support On/Off timer, Sleep timer etc	
Remote Control function support for full OSD features		Remote control shortcut keys support: menu, signal source selection, electronic program guides, mute, etc. OSD menu support: English ,Portuguese, Spanish	
Wall Mount		Optional	
Power Supply	INPUT		110V-240V 50/60Hz
	Power Consumption		180W
	Power Saving		<1W
Certification		CE, CB, FCC, UL, Rohs	
Accessories		remote control / user manual / power cord / battery	
Mechanical	Package Dimension		1520*8700*185mm
Loading Qty	20GP/40GP/40HQ		120/242/282pcs



Picture		
Model number		SIT 520
Display Feature	LED panel	55inch
	Display Size	1209.6(H)×680.4(V)mm
	Aspect ratio	16:9 FHD
	Resolution	1920(H)×1080(V) RGB
	Pixel Pitch	0.630(H) x 0.630(V)
	Maximum Colors	16.7M
	Horizontal Freq.	44KHz~53KHz
	Vertical Freq.	50Hz~66Hz
	Brightness	300 cd/m2
	Contrast	5000:1
	Viewing Angle	178°/178°(UP/DOWN LEFT/RIGHT)
	Response time	8.5ms
TV SYSTEM	COLOR SYSTEM	PAL,NTSC,SECAM
	Sound System	M,N,B/G,D/K,I
	Stereo System	Stereo



	V-CHIP		No
	TELETEXT		Optional
	STORAGE CHANNEL		200
Video Features	Video Processing & Conversion		3D digital comb filter and 3D noise reduction function
Audio Speaker System	Speaker Type		Inseparable
	Maximum Audio Output		15W × 2
	Sound multiplex circuit		Standard/Dynamic/Soft/User
Terminals	Video in	RF:TV/CATV 75ohms connector	1
		AV : RCA 75ohms composite video	3 RCA(Yellow,Red,White) and 1 mini AV jack
		S-Video : 4-pin DIN	1
		YPbPr: RCA	1
		HDMI	x2
		USB	1
	AUDIO IN	L/R RCA for YPbPr	No
		L/R RCA for S-Video& AV	1
		L/R RCA for S-Video& AV&YPbPr	1
		PC Audio in 3.5mm Jack:x1	1
	OUTPUT	Coaxial Audio output:	No
		EARPHONE OUTPUT	1
		AV OUTPUT	1
		YPbPr	480i, 480P, 576i,720P, 720P, 1080iand 1080p



INPUT FORMAT	HDMI	480i, 480P, 576i, 720P, 720P, 1080i and 1080p	
	PC	VGA 60/75Hz, SVGA 60/75Hz, XGA 60/75Hz, WXGA 60/75Hz, SXGA 60/75Hz	
	AV/S-Video/SCART	640*480i 50Hz/60Hz	
	USB	MUSIC	MP3/WMA/M4A/AAC
		Picture	JPEG/BMP/PNG
		Movie	MPEG1/MPEG2/MPEG4, RM, RMVB, MOV, MJPEG, Divx
		TXT	Optional
	Other	Software upgrade	
Other Features		Support On/Off timer, Sleep timer etc	
Remote Control function support for full OSD features		Remote control shortcut keys support: menu, signal source selection, electronic program guides, mute, etc. OSD menu support: English, Portuguese, Spanish	
Wall Mount		Optional	
Power Supply	INPUT	100V-240V 50/60Hz	
	Power Consumption	<110W	
	Power Saving	<0.5W	
Certification		CE, CB, FCC, UL, Rohs	
Accessories		remote control / user manual / power cord / battery	
Mechanical	Package Dimension	1520*8700*185mm	
Loading Qty	20GP/40GP/40HQ	120/242/282pcs	

📍 Cairo, EGYPT. 3 Abou Tamam st., Hadayak El Kobba. (+2) 02 233 023 99 (+2) 01 22 22 00 787

📍 Shenzhen, CHINA. 1709B Saige st., Hua Qiang Bel, Futian District.

📍 Kowloon, Hong Kong. 5/f Hang Pont Commercial Building, 31 Tonkin st., Cheung Sha Wan.

📍 Vietnam : 0084-1688370651 📍 Malaysia : (+6)13416407902 📍 Kuwait : (+9)6560617291 📍 Sudan : (+2)49910745498